College of William and Mary W&M Publish

VIMS Data

7-11-2014

Cruise: YR130521, Stations: S5100- S5124, Clay Bank, York River Virginia 6-hour MUDBED Calibration Survey bracketing an Ebb Tide

Grace M. Cartwright
Virginia Institute of Marine Science, gracec@vims.edu

Carl T. Friedrichs

Virginia Institute of Marine Science, carl.friedrichs@vims.edu

Follow this and additional works at: http://publish.wm.edu/data

Part of the Environmental Sciences Commons, Marine Biology Commons, and the Oceanography Commons

Recommended Citation

Cartwright, G.M., and Friedrichs, C.T., 2014. Cruise: YR130521, Stations: S5100- S5124, Clay Bank, York River Virginia 6-hour MUDBED Calibration Survey bracketing an Ebb Tide. Virginia Institute of Marine Science, College of William and Mary. http://doi.org/10.21220/V5D597

This Data is brought to you for free and open access by W&M Publish. It has been accepted for inclusion in VIMS Data by an authorized administrator of W&M Publish. For more information, please contact wmpublish@wm.edu.

Authors:

Cartwright, Grace M., Friedrichs, Carl T.

Title:

Cruise: YR130521, Stations: S5100- S5124, Clay Bank, York River Virginia 6-hour MUDBED Calibration Survey bracketing an Ebb Tide

URI:

http://hdl.handle.net/10288/20238

Location (place name):

York River, VA

Location (bounding box coordinates):

37° 07 23' N, 076° 09 12'W; 37° 13 33' N, 076° 18 28'W; 37° 39 12' N, 076° 54 00'W; 37° 34 54' N, 076° 59 24'W

Start Date:

2013 May 21

Abstract:

Dataset consists of profile and water column burst data and bottom burst data collected as part of a 6-hour anchor station survey in support of an Acoustic Doppler Velicometer (ADV) tripod deployed in nearby location.

Description of Data:

During each station in the survey a profile or bottom time series was collected with a suite of instrumentation including: a YSI 6600 CTD, a YSI Castaway CTD, a Sequia LISST 100X, RDI 1200 kHz ADCP, PICS floc camera system and a Sontek ADVOcean and a Nortek Vector. The raw data of profile stations are processed to provide a smooth profile of data throughout the water column and a series of between 2 to 5 minute bursts from various heights in the water column. Bottom bursts are time series collected when the profiler was resting on the seafloor. Total Suspended Solids (and fixed solids) were sampled from depth to calibrate the acoustic backscatter. The "logbook" is the hand written field notes and instrument setup documents. The "Profiler Set up" is a log of the location and serial number of the instruments mounted on the profiler. The "Consecutive Station Log" is an excel spreadsheet of the metadata associated with each station in the survey. Excel

spreadsheet "Averaged Data" contains burst averaged data and statistics from the water column and bottom bursts. Raw and processed data from each instrument are zipped in a folder, or series of folders, identified by the type and serial number of the instrument. All times are Eastern Standard Time (EST).

Funding sources:

NSF grants OCE-0536572 and OCE-1061781

Publication Type:

Data

Related Material:

Doi:

Subject Keywords:

Sediment transport; acoustic backscatter; conductivity temperature and depth sensor; CTD; Acoustic Doppler Current Profiler; ADCP; LISST; settling velocity; suspended size distribution; TSS; Total Suspended Solids

Preferred Citation:

Cartwright, G.M., and Friedrichs, C.T., 2014. Cruise: YR130521, Stations: S5100-S5124, Clay Bank, York River Virginia 6-hour MUDBED Calibration Survey bracketing an Ebb Tide. http://hdl.handle.net/10288/20238